



Wireless Crane Scale

Model: OCS-SWL6




Main technical data

Accuracy Standard	According to OIML class III
Display	LCD with backlight
Wireless Distance	Up to 200m without obstacle
Filtering	Low, Medium or High selectable
Resolution	2000 to 3000 divisions standard up to 15,000 available
Zero Range	Auto/Manual setting, from 4% to 100%F.S.
Tare Range	100% F.S.
Overload Indication	100% F.S. + 9e
Max. Safety Load	125% F.S.
Ultimate Load	400% F.S.
Scale Battery Type	DC 6V/4.5Ah rechargeable Lead-Acid battery
Indicator Battery	DC 6V/7Ah rechargeable Lead-Acid battery
Battery charger	Input:AC100-240V 50/60Hz Output:850mA
Printer	Standard parallel print interface(EPSON printer)
Operating Temperature Range	- 20℃ ~ + 50℃
Operating Humidity	≤85% RH under 20℃
Radio Frequency	433MHz

Features

- ◆Seamless steel pipe enclosure for maximum protection.
- ◆Manu operation mode, calibration, saving, searching, printing, easy to operate.
- ◆Indicator Adopts $\Sigma-\Delta$ A/D conversion technology.
- ◆Able to setup zero(auto/manual) range, filtering range.
- ◆Weighing data save protection in case of power off.
- ◆ Battery charger with several protection modes to extend life of rechargeable battery.
- ◆Standard RS232 communication interface(optional).
- ◆Portable design, indicator packed in portable carry case, easy to operate outdoor.
- ◆Gathering up to data records of 2000 weighings, records can be sorted, searched and printed.
- ◆Power saving mode, indicator will turn off automatically after 30minutes with no operation.
- ◆ With 32 channels optional, so 32 crane scales can operated independently in the same airplace without interface.



Dimensions and Specifications

MODEL	Cap.(kg)	Resolution (kg)	A(mm)	C(mm)	E(mm)	H(mm)	Φ(kg)	G.W.(kg)
OCS-SWL6-1	1000	0.5	95	33	145	445	270	33
OCS-SWL6-2	2000	1	95	33	145	445	270	33
OCS-SWL6-3	3000	1	95	40	145	445	270	34
OCS-SWL6-5	5000	2	120	50	155	485	298	45
OCS-SWL6-10	10000	5	124	60	170	655	325	55
OCS-SWL6-15	15000	5	225	70	170	855	325	75
OCS-SWL6-20	20000	10	225	85	170	920	325	85
OCS-SWL6-30	30000	10	260	105	200	1055	375	125