

Eoslift

Semi-electric Pallet Stacker

S15J



Eoslift

Eoslift Automation Technology Corp.
No.99, Yanjia Road, Yuanlong Town, Haiyan, Zhejiang
Province, China 314317
Tel: +86 573 8622 9999
Fax: +86 573 8622 2900
info@eoslift.com
www.eoslift.com

Hotline: 400-626-9090

Eoslift USA Corporation
1590 S.Milliken Avenue, Unit H, Ontario, California 91761
Tel: +1-888-264-5008
Fax: +1-781-780-5915
sales@eoslift.us
www.eoslift.us

Product features



Wide Applicability

- Used for loading goods onto or unloading goods from pallets and stacking goods
- Compact truck body, especially suitable for narrow aisles and small spaces
- Straddle and forged forks available

Safe and Comfort

- Hydraulic reservoir with filter, effectively prevents contamination by foreign matters, ensuring a long service life of the hydraulic system
- With a transparent acrylic guarding plate, to provide a broader vision and better protection
- Anti-pressure caster frame, intimate protection handle ergonomically designed to ensure maximum safety and comfort with a mechanical assist steering, steering more easily
- Ergonomic handle to ensure optimum safety and comfort
- Mechanically assisted steering system for easy travel

Stable and Reliable

- Efficient and energy-saving power unit
- Overload protection
- Throttle valve with pressure compensation function enables stable and reliable lowering
- Frame constructed of high-strength C type steel, especially for double frame series which will be more stable when lifting and lowering

General Information			
Model		S15J	
Rated capacity	lb.	3300	
Load center	in.	23.6	
Service weight	lb.	990	
Size			
Minimum fork height	H1	in.	1.4
Maximum fork height	H	in.	118.1
Lowered Mast Height	H2	in.	81.1
Fork length	L	in.	45.3
Overall fork width	B3	in.	8.3-32.7
Length of the stacker	L1	in.	69.6
Width of the stacker	B2	in.	41.3-57.1
Minimum turning radius	R	in.	52.6
Battery	V/Ah		12/120

